



PRODUCT INFORMATION

D104

Transfer Tape

Description

A stabilized, transfer adhesive with high tack, peel and holding power. Designed to adhere to a wide variety of surfaces, including metals and engineering plastics. Good chemical and plasticizer resistance, long-term aging and ability to withstand environmental extremes.

Features

- Performs over wide temperature range
- Heavy adhesive mass aids adhesion to rough or irregular surfaces
- Not recommended for cold weather applications. Room Temperature Storage.

Adhesive	5 mils Stabilized Acrylic	.127 mm
Liner	50# Brown Kraft	
Total Thickness	5.0 mils	.127 mm
Adhesion to Stainless Steel	75 oz/in	N/25mm
Service Temperature Range	-50°F- 250°F	-46°C - 121°C

Application

Bonding and mounting nameplates, gasket materials, fabrics; splicing.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.