



PRODUCT INFORMATION

S292CLA Polyester Silicone Splicing Tape

Description

Clear single coated polyester high temperature silicone splicing tape provides a superior bond to the most difficult silicone release surfaces and interliners.

Features

- Superior adhesion to silicone release surfaces
- Conformable polyester film is durable and resists tearing and punctures
- Chemically resistant
- Stable adhesive resists flow, oozing or slippage

Backing	1 mil Polyester	.025 mm
Adhesive	1.5 mils Silicone	.036 mm
180° Peel Adhesion to Stainless Steel (Min)	40 oz/in	11N/25mm
Temperature Resistance	400°F	204°C
Color	Clear	
Total Tape Thickness	2.5 mils	.061 mm

Application

Designed to perform splicing applications on difficult silicone release surfaces even in high temperature environments.

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith. Materials should be stored at 70°F (21°C) with 50% relative humidity.