



# PRODUCT INFORMATION

## #S950BL Removable Blue Polyester Protective Tape

### Description

Single coated, self-wound, blue 1.5 mil polyester coated with a high performance low tack removable adhesive system.

### Features

Product S950BL is a low adhesion removable tape designed to be used as a protective mask. The product exhibits excellent high temperature resistance with clean removal even after being bonded for extended periods of time. The 1.5 mil blue polyester offers good conformability and strength for protective mask applications. The acrylic adhesive is moisture resistant and exhibits good long term UV resistance.

Carrier	1.5 mil Blue Polyester	.038 mm
Adhesive	1.0 mil Acrylic	.025 mm
Total Tape Thickness	2.5 mils	.063 mm
Adhesion to Stainless	0.5 oz/in	0.14 N/25mm
Service Temperature Short Term (minutes, hours) Long Term (days, weeks)	400°F 300°F	204°C 148°C
Color	Blue	

### Application

To achieve ultimate adhesion, the bonding surface should be dry, clean and free of dirt and oils. The strength of the adhesive bond is dependent on the amount of surface area directly contacting the adhesive. Firm pressure is recommended to obtain good adhesive to surface contact.

†Note: Values should not be used for specification purposes. Each user should make their own test to determine the products suitability for their own intended use and shall assume all risks and liabilities in connection therewith.

Materials should be stored at 70°F (21°C) with 50% relative humidity.

800-545-8273 · 262-835-0748 · Fax: 262-835-0749 · [www.specialtytapes.net](http://www.specialtytapes.net)  
4221 Courtney Road · Franksville, WI 53126